

BP10880 Rechargeable C Battery

Specifications	
Model	BP10880
Nominal voltage	3.7V
Nominal capacity	700mAh
Minimum Capacity	650mAh
Combination	One-piece design
Additional Feature	Type-C charge
Storage Temperature	(1 month) -20°C~50°C
Max. Continuous Discharge Current	2A
Internal Resistance	≤120m Ω
Weight	20g
Shipment Voltage	>3.5V
Operating environment	Charging temperature: 0°C~45°C Discharge temperature: -20°C~60°

Features and Benefits

1. Narrow10880 Size: Extended cylindrical form factor (10.55mm x 87.7mm) with a higher 3.7V, 700mAh capacity.
2. Integrated Type-C Charging: Features a built-in Type-C port for convenient, faster USB charging (~600mA).
3. Built-in Protection Circuit: Includes safeguards against overcharge, over-discharge, overcurrent, and short circuits.
4. LED Charging Indicator: Simple red/green LED lights to display charging status and full charge.
5. Wide Operating Range: Suitable for discharge in temperatures from -20°C to 60°C.
6. Compliance & Safety: Manufactured to meet GB 31241-2014 safety standards and passes key safety tests.



Dimensional



H: 87.7mm
D: 10.55mm
H1: 1.6mm
D1: 3.00mm